

CoCrPtB of a magnetic disk. In the structure of the magnetic disk, when the Ru layer having a thickness of about 0.5 to 1 nm is allowed to intervene as the magnetic coupling layer between the recording layer and the magnetization-stabilizing layer, the exchange coupling is effected in an antiferromagnetic manner between the recording layer and the magnetization-stabilizing layer. Therefore, the layers have antiparallel magnetization, and hence the magnetization of the recording layer is stabilized by the magnetization-stabilizing layer. It is described in this literature that the antiferromagnetic exchange coupling effected by the Ru layer further thermally stabilizes the magnetization of the recording layer, making it possible to improve the recording and reproduction characteristics of the magnetic disk.

Please replace paragraph [0012] as follows:

[0012] As a result of repeated investigations performed by the present inventors in order to further improve the magnetic disk having the conventional type structure, it has been found out that the exchange coupling force, which is generated between the ferromagnetic atom-rich layer and the recording layer, is remarkably raised by forming the ferromagnetic atom-rich layer formed with the material having the high ferromagnetic atom concentration as compared with the ferromagnetic material for forming the recording layer, in place of the magnetization-stabilizing layer. The exchange coupling force, which is generated between the ferromagnetic atom-rich layer and the recording layer as described above, is larger than the exchange coupling force which acts between the recording layer and the magnetization-stabilizing layer of the magnetic disk having the conventional type structure. As described above, the strong exchange coupling force is generated between the recording layer and the ferromagnetic atom-rich layer, and hence it is possible to stabilize the magnetization of the recording layer. Therefore, the thermal stability of the recording layer is further enhanced as compared with the conventional magnetic disk, making it possible to realize further advanced high density recording. In the present invention, the term "ferromagnetic atom" means the

element which exhibits the ferromagnetic property in the form of simple substance.

Specifically, the ferromagnetic atom includes cobalt (Co), nickel (Ni), and iron (Fe).

Please replace paragraph [0013] as follows:

[0013] The ferromagnetic atom-rich layer is formed with the ferromagnetic material which has the high ferromagnetic atom concentration as compared with the ferromagnetic material for forming the recording layer. For example, when the recording layer is formed of a ferromagnetic material containing Co, Ni, or Fe, the ferromagnetic atom-rich layer can be formed of a ferromagnetic material containing a ferromagnetic atom such as Co, Ni, and Fe at a higher concentration as compared with the recording layer. The ferromagnetic atom-rich layer can be also formed of a metal simple substance such as Co, Ni, and Fe or CoNiFe alloy. Alternatively, the ferromagnetic atom-rich layer may be formed of an alloy containing a transition metal and Co, Ni, or Fe. In this case, the transition metal may be a noble metal such as Pt, Au, Ag, Cu, and Pd. In the present invention, when the ferromagnetic atom concentration of the ferromagnetic material for constructing the ferromagnetic atom-rich layer is higher than the ferromagnetic atom concentration of the magnetic material for constructing the recording layer, it is possible to obtain the effect to enhance the exchange coupling force generated between the ferromagnetic atom-rich layer and the recording layer. However, in order to obtain a sufficient effect in view of the results obtained in the embodiments as described later on, it is desirable that the ferromagnetic atom concentration of the ferromagnetic material for constructing the ferromagnetic atom-rich layer is higher than the ferromagnetic atom concentration of the ferromagnetic material for constructing the recording layer by not less than 19 % as represented by an absolute value. Especially, it is desirable that the ferromagnetic atom concentration of the ferromagnetic atom-rich layer is 100 %. Owing to the ferromagnetic atom-rich layer as described above, the exchange coupling force, which is generated between the ferromagnetic atom-rich layer and the

54B
C3
C4
D

recording layer, is larger than the exchange coupling force which is generated between the magnetization-stabilizing layer and the recording layer of the conventional magnetic disk. Therefore, the thermal stability of the recording layer is further enhanced as compared with the conventional technique, making it possible to realize further advanced high density recording.

Please replace paragraph [0016] as follows:

54B
C3
C4
D

09944193.01E502

[0016] As a result of investigations performed by the present inventors, it has been found out that the exchange coupling between the recording layer and the magnetization-stabilizing layer can be remarkably improved by intervening a several-atoms-layered Co layer at an interface between the Ru layer (non-magnetic layer) and the recording layer and/or an interface between the Ru layer (non-magnetic layer) and the magnetization-stabilizing layer of the magnetic disk having the conventional type structure. The layer to be intervened at the interface is not limited to Co, which may be composed of a material having a high ferromagnetic atom concentration as compared with the recording layer, and which may be constructed with a variety of substances capable of improving the exchange coupling between the recording layer and the magnetization-stabilizing layer as described later on. That is, when the magnetic recording medium is provided with the magnetization-stabilizing layer, the exchange coupling force between the recording layer and the magnetization-stabilizing layer can be improved by positioning the ferromagnetic atom-rich layer at the interface. In this specification, the ferromagnetic atom-rich layer is also referred to as "enhancing layer", because the ferromagnetic atom-rich layer is also provided with the function to enhance the exchange coupling between the recording layer and the magnetization-stabilizing layer when the magnetization-stabilizing layer is provided.

Please replace paragraph [0017] as follows:

Sub
C7
B4

[0017] According to the knowledge of the present inventors, the reason why the ferromagnetic atom-rich layer, i.e., the enhancing layer, which is positioned between the magnetization-stabilizing layer and the recording layer, successfully improves the exchange coupling between the recording layer and the magnetization-stabilizing layer is as follows. In the case of the conventional type magnetic disk, the recording layer of CoCrPtB and the magnetization-stabilizing layer of CoCrPtB are stacked with the Ru layer intervening therebetween. In this case, the recording layer and the magnetization-stabilizing layer effect the exchange coupling via the Ru atom layer. It is considered that the exchange coupling is effected on the basis of the fact that the electron orbits are coupled between the Co atoms in the recording layer and the magnetization-stabilizing layer via the Ru atoms. Such a coupling is also found, for example, in the coupling in an artificial lattice of a GMR head.

Please replace paragraph [0030] as follows:

Sub
C6
B3

[0030] The magnetic recording medium of the present invention comprises the lattice spacing-adjusting layer which is formed between the underlying base layer and the recording layer and which is formed of the ferromagnetic material to make control so that the difference in lattice spacing between the lattice spacing-adjusting layer and the underlying base layer is smaller than the difference in lattice spacing between the recording layer and the underlying base layer. The lattice spacing-adjusting layer as described above mitigates the lattice strain between the underlying base layer and the recording layer, and the crystalline orientation of the recording layer is improved thereby. Accordingly, it is possible to increase the coercive force of the recording layer. The magnetic recording medium as described above is formed of the ferromagnetic material in the same manner as the magnetization-stabilizing layer of the in-plane magnetic recording medium having the conventional type structure. Therefore, it is possible to stabilize the magnetization of the recording layer. That is, the lattice spacing-adjusting layer has a function to stabilize the magnetization of the

slr3
C6
conf
B-5
recording layer, in addition to a function as a seed layer to act so that the lattice strain between the underlying base layer and the recording layer, i.e., the discrepancy of lattice spacing is mitigated. Therefore, the high density recording can be put into practice by using the magnetic recording medium of the present invention, because the minute magnetic domain formed in the recording layer can be stably retained. In the present invention, the term "lattice spacing" means the lattice spacing on the orientation plane.

Please replace paragraph [0035] as follows:

09944193-012502
B-5
[0035] It is desirable for the magnetic recording medium according to the second aspect of the present invention that a relationship of $M_{s1} > M_{s2}$ is satisfied provided that saturation magnetization of the lattice spacing-adjusting layer is represented by M_{s1} , and saturation magnetization of the recording layer is represented by M_{s2} . For this purpose, it is desirable that the lattice spacing-adjusting layer is formed so that a ratio of magnetic atom contained in the lattice spacing-adjusting layer is larger than a ratio of magnetic atom contained in the recording layer. Accordingly, it is possible to further increase the exchange coupling force between the recording layer and the lattice spacing-adjusting layer. In the case of the conventional type medium, the recording layer and the magnetization-stabilizing layer are composed of the same material, in which the composition and the crystal structure are also the same. The recording layer and the magnetization-stabilizing layer are subjected to exchange coupling via the Ru layer. It is considered that the exchange coupling is based on the fact that the electron orbits are coupled to one another for the Co atoms in the recording layer and the magnetization-stabilizing layer by the aid of the Ru atoms. In the present invention, the ratio of the magnetic element in the lattice spacing-adjusting layer is made higher than the ratio of the magnetic element in the recording layer to increase the amount of magnetic element which contributes to the exchange coupling. Therefore, the exchange coupling force between the recording layer and the lattice spacing-adjusting layer is

increased as compared with the exchange coupling force between the recording layer and the magnetization-stabilizing layer of the conventional type medium. Accordingly, it is possible to improve the thermal stability as compared with the conventional type medium.

Please replace paragraph [0043] as follows:

[0043] Each of the magnetic recording media according to the first and second aspects of the present invention has a magnetic characteristic which is represented by a hysteresis loop as depicted by a magnetization curve as shown in Figs. 4 and 16. The following description will be made on the basis of a case of the magnetic recording medium according to the first aspect. However, an equivalent relationship is also affirmed between the lattice spacing-adjusting layer and the recording layer of the magnetic recording medium according to the second aspect. In the hysteresis loop shown in Fig. 4, a point, at which a rate of change of magnetization with respect to the external magnetic field exhibits a local maximum when the external magnetic field is lowered after magnetization of the magnetic recording medium is saturated, exists in an area of positive magnetic field. When the magnetization of the magnetic recording medium is saturated, both of the magnetizations of the recording layer and the ferromagnetic atom-rich layer (or the lattice spacing-adjusting layer) are parallel. The magnetization of the ferromagnetic atom-rich layer (or the lattice spacing-adjusting layer) is inverted due to the exchange coupling force exerted between the ferromagnetic atom-rich layer (or the lattice spacing-adjusting layer) and the recording layer in the area in which the rate of change of magnetization exhibits the local maximum as the external magnetic field is lowered. In the residual magnetization state, the thermal stability of the magnetization of the recording layer is improved owing to the exchange coupling force as described above. Further, a minor hysteresis loop as shown in Fig. 4 may be observed in the area in which the rate of change of magnetization is locally maximized. The minor hysteresis loop is shown in Fig. 5A. The exchange coupling magnetic field H_{ex} , which is

SUB
 C.G.
 COST
 B-7

determined from the central point of the minor hysteresis loop, is increased in accordance with the increase of the exchange coupling force between the ferromagnetic atom-rich layer (or the lattice spacing-adjusting layer) and the recording layer. Therefore, it is indicated that the larger the exchange coupling magnetic field is, the larger the thermal stability is. The exchange coupling magnetic field H_{ex} is not less than 1 kOe, preferably not less than 1.5 kOe, which is remarkably larger than that of the conventional type magnetic recording medium. Therefore, it is appreciated that the magnetic recording medium of the present invention is excellent in thermal stability.

Please replace paragraph [0048] as follows:

[0048] Fig. 1 shows a cross-sectional structure of a magnetic disk according to a first embodiment.

09/944,193
 0048
 0049
 0050
 0051
 0052
 0053
 0054
 0055
 0056
 0057
 0058
 0059
 0060
 0061
 0062
 0063
 0064
 0065
 0066
 0067
 0068
 0069
 0070
 0071
 0072
 0073
 0074
 0075
 0076
 0077
 0078
 0079
 0080
 0081
 0082
 0083
 0084
 0085
 0086
 0087
 0088
 0089
 0090
 0091
 0092
 0093
 0094
 0095
 0096
 0097
 0098
 0099
 0100
 0101
 0102
 0103
 0104
 0105
 0106
 0107
 0108
 0109
 0110
 0111
 0112
 0113
 0114
 0115
 0116
 0117
 0118
 0119
 0120
 0121
 0122
 0123
 0124
 0125
 0126
 0127
 0128
 0129
 0130
 0131
 0132
 0133
 0134
 0135
 0136
 0137
 0138
 0139
 0140
 0141
 0142
 0143
 0144
 0145
 0146
 0147
 0148
 0149
 0150
 0151
 0152
 0153
 0154
 0155
 0156
 0157
 0158
 0159
 0160
 0161
 0162
 0163
 0164
 0165
 0166
 0167
 0168
 0169
 0170
 0171
 0172
 0173
 0174
 0175
 0176
 0177
 0178
 0179
 0180
 0181
 0182
 0183
 0184
 0185
 0186
 0187
 0188
 0189
 0190
 0191
 0192
 0193
 0194
 0195
 0196
 0197
 0198
 0199
 0200
 0201
 0202
 0203
 0204
 0205
 0206
 0207
 0208
 0209
 0210
 0211
 0212
 0213
 0214
 0215
 0216
 0217
 0218
 0219
 0220
 0221
 0222
 0223
 0224
 0225
 0226
 0227
 0228
 0229
 0230
 0231
 0232
 0233
 0234
 0235
 0236
 0237
 0238
 0239
 0240
 0241
 0242
 0243
 0244
 0245
 0246
 0247
 0248
 0249
 0250
 0251
 0252
 0253
 0254
 0255
 0256
 0257
 0258
 0259
 0260
 0261
 0262
 0263
 0264
 0265
 0266
 0267
 0268
 0269
 0270
 0271
 0272
 0273
 0274
 0275
 0276
 0277
 0278
 0279
 0280
 0281
 0282
 0283
 0284
 0285
 0286
 0287
 0288
 0289
 0290
 0291
 0292
 0293
 0294
 0295
 0296
 0297
 0298
 0299
 0300
 0301
 0302
 0303
 0304
 0305
 0306
 0307
 0308
 0309
 0310
 0311
 0312
 0313
 0314
 0315
 0316
 0317
 0318
 0319
 0320
 0321
 0322
 0323
 0324
 0325
 0326
 0327
 0328
 0329
 0330
 0331
 0332
 0333
 0334
 0335
 0336
 0337
 0338
 0339
 0340
 0341
 0342
 0343
 0344
 0345
 0346
 0347
 0348
 0349
 0350
 0351
 0352
 0353
 0354
 0355
 0356
 0357
 0358
 0359
 0360
 0361
 0362
 0363
 0364
 0365
 0366
 0367
 0368
 0369
 0370
 0371
 0372
 0373
 0374
 0375
 0376
 0377
 0378
 0379
 0380
 0381
 0382
 0383
 0384
 0385
 0386
 0387
 0388
 0389
 0390
 0391
 0392
 0393
 0394
 0395
 0396
 0397
 0398
 0399
 0400
 0401
 0402
 0403
 0404
 0405
 0406
 0407
 0408
 0409
 0410
 0411
 0412
 0413
 0414
 0415
 0416
 0417
 0418
 0419
 0420
 0421
 0422
 0423
 0424
 0425
 0426
 0427
 0428
 0429
 0430
 0431
 0432
 0433
 0434
 0435
 0436
 0437
 0438
 0439
 0440
 0441
 0442
 0443
 0444
 0445
 0446
 0447
 0448
 0449
 0450
 0451
 0452
 0453
 0454
 0455
 0456
 0457
 0458
 0459
 0460
 0461
 0462
 0463
 0464
 0465
 0466
 0467
 0468
 0469
 0470
 0471
 0472
 0473
 0474
 0475
 0476
 0477
 0478
 0479
 0480
 0481
 0482
 0483
 0484
 0485
 0486
 0487
 0488
 0489
 0490
 0491
 0492
 0493
 0494
 0495
 0496
 0497
 0498
 0499
 0500
 0501
 0502
 0503
 0504
 0505
 0506
 0507
 0508
 0509
 0510
 0511
 0512
 0513
 0514
 0515
 0516
 0517
 0518
 0519
 0520
 0521
 0522
 0523
 0524
 0525
 0526
 0527
 0528
 0529
 0530
 0531
 0532
 0533
 0534
 0535
 0536
 0537
 0538
 0539
 0540
 0541
 0542
 0543
 0544
 0545
 0546
 0547
 0548
 0549
 0550
 0551
 0552
 0553
 0554
 0555
 0556
 0557
 0558
 0559
 0560
 0561
 0562
 0563
 0564
 0565
 0566
 0567
 0568
 0569
 0570
 0571
 0572
 0573
 0574
 0575
 0576
 0577
 0578
 0579
 0580
 0581
 0582
 0583
 0584
 0585
 0586
 0587
 0588
 0589
 0590
 0591
 0592
 0593
 0594
 0595
 0596
 0597
 0598
 0599
 0600
 0601
 0602
 0603
 0604
 0605
 0606
 0607
 0608
 0609
 0610
 0611
 0612
 0613
 0614
 0615
 0616
 0617
 0618
 0619
 0620
 0621
 0622
 0623
 0624
 0625
 0626
 0627
 0628
 0629
 0630
 0631
 0632
 0633
 0634
 0635
 0636
 0637
 0638
 0639
 0640
 0641
 0642
 0643
 0644
 0645
 0646
 0647
 0648
 0649
 0650
 0651
 0652
 0653
 0654
 0655
 0656
 0657
 0658
 0659
 0660
 0661
 0662
 0663
 0664
 0665
 0666
 0667
 0668
 0669
 0670
 0671
 0672
 0673
 0674
 0675
 0676
 0677
 0678
 0679
 0680
 0681
 0682
 0683
 0684
 0685
 0686
 0687
 0688
 0689
 0690
 0691
 0692
 0693
 0694
 0695
 0696
 0697
 0698
 0699
 0700
 0701
 0702
 0703
 0704
 0705
 0706
 0707
 0708
 0709
 0710
 0711
 0712
 0713
 0714
 0715
 0716
 0717
 0718
 0719
 0720
 0721
 0722
 0723
 0724
 0725
 0726
 0727
 0728
 0729
 0730
 0731
 0732
 0733
 0734
 0735
 0736
 0737
 0738
 0739
 0740
 0741
 0742
 0743
 0744
 0745
 0746
 0747
 0748
 0749
 0750
 0751
 0752
 0753
 0754
 0755
 0756
 0757
 0758
 0759
 0760
 0761
 0762
 0763
 0764
 0765
 0766
 0767
 0768
 0769
 0770
 0771
 0772
 0773
 0774
 0775
 0776
 0777
 0778
 0779
 0780
 0781
 0782
 0783
 0784
 0785
 0786
 0787
 0788
 0789
 0790
 0791
 0792
 0793
 0794
 0795
 0796
 0797
 0798
 0799
 0800
 0801
 0802
 0803
 0804
 0805
 0806
 0807
 0808
 0809
 0810
 0811
 0812
 0813
 0814
 0815
 0816
 0817
 0818
 0819
 0820
 0821
 0822
 0823
 0824
 0825
 0826
 0827
 0828
 0829
 0830
 0831
 0832
 0833
 0834
 0835
 0836
 0837
 0838
 0839
 0840
 0841
 0842
 0843
 0844
 0845
 0846
 0847
 0848
 0849
 0850
 0851
 0852
 0853
 0854
 0855
 0856
 0857
 0858
 0859
 0860
 0861
 0862
 0863
 0864
 0865
 0866
 0867
 0868
 0869
 0870
 0871
 0872
 0873
 0874
 0875
 0876
 0877
 0878
 0879
 0880
 0881
 0882
 0883
 0884
 0885
 0886
 0887
 0888
 0889
 0890
 0891
 0892
 0893
 0894
 0895
 0896
 0897
 0898
 0899
 0900
 0901
 0902
 0903
 0904
 0905
 0906
 0907
 0908
 0909
 0910
 0911
 0912
 0913
 0914
 0915
 0916
 0917
 0918
 0919
 0920
 0921
 0922
 0923
 0924
 0925
 0926
 0927
 0928
 0929
 0930
 0931
 0932
 0933
 0934
 0935
 0936
 0937
 0938
 0939
 0940
 0941
 0942
 0943
 0944
 0945
 0946
 0947
 0948
 0949
 0950
 0951
 0952
 0953
 0954
 0955
 0956
 0957
 0958
 0959
 0960
 0961
 0962
 0963
 0964
 0965
 0966
 0967
 0968
 0969
 0970
 0971
 0972
 0973
 0974
 0975
 0976
 0977
 0978
 0979
 0980
 0981
 0982
 0983
 0984
 0985
 0986
 0987
 0988
 0989
 0990
 0991
 0992
 0993
 0994
 0995
 0996
 0997
 0998
 0999
 1000
 1001
 1002
 1003
 1004
 1005
 1006
 1007
 1008
 1009
 1010
 1011
 1012
 1013
 1014
 1015
 1016
 1017
 1018
 1019
 1020
 1021
 1022
 1023
 1024
 1025
 1026
 1027
 1028
 1029
 1030
 1031
 1032
 1033
 1034
 1035
 1036
 1037
 1038
 1039
 1040
 1041
 1042
 1043
 1044
 1045
 1046
 1047
 1048
 1049
 1050
 1051
 1052
 1053
 1054
 1055
 1056
 1057
 1058
 1059
 1060
 1061
 1062
 1063
 1064
 1065
 1066
 1067
 1068
 1069
 1070
 1071
 1072
 1073
 1074
 1075
 1076
 1077
 1078
 1079
 1080
 1081
 1082
 1083
 1084
 1085
 1086
 1087
 1088
 1089
 1090
 1091
 1092
 1093
 1094
 1095
 1096
 1097
 1098
 1099
 1100
 1101
 1102
 1103
 1104
 1105
 1106
 1107
 1108
 1109
 1110
 1111
 1112
 1113
 1114
 1115
 1116
 1117
 1118
 1119
 1120
 1121
 1122
 1123
 1124
 1125
 1126
 1127
 1128
 1129
 1130
 1131
 1132
 1133
 1134
 1135
 1136
 1137
 1138
 1139
 1140
 1141
 1142
 1143
 1144
 1145
 1146
 1147
 1148
 1149
 1150
 1151
 1152
 1153
 1154
 1155
 1156
 1157
 1158
 1159
 1160
 1161
 1162
 1163
 1164
 1165
 1166
 1167
 1168
 1169
 1170
 1171
 1172
 1173
 1174
 1175
 1176
 1177
 1178
 1179
 1180
 1181
 1182
 1183
 1184
 1185
 1186
 1187
 1188
 1189
 1190
 1191
 1192
 1193
 1194
 1195
 1196
 1197
 1198
 1199
 1200
 1201
 1202
 1203
 1204
 1205
 1206
 1207
 1208
 1209
 1210
 1211
 1212
 1213
 1214
 1215
 1216
 1217
 1218
 1219
 1220
 1221
 1222
 1223
 1224
 1225
 1226
 1227
 1228
 1229
 1230
 1231
 1232
 1233
 1234
 1235
 1236
 1237
 1238
 1239
 1240
 1241
 1242
 1243
 1244
 1245
 1246
 1247
 1248
 1249
 1250
 1251
 1252
 1253
 1254
 1255
 1256
 1257
 1258
 1259
 1260
 1261
 1262
 1263
 1264
 1265
 1266
 1267
 1268
 1269
 1270
 1271
 1272
 1273
 1274
 1275
 1276
 1277
 1278
 1279
 1280
 1281
 1282
 1283
 1284
 1285
 1286
 1287
 1288
 1289
 1290
 1291
 1292
 1293
 1294
 1295
 1296
 1297
 1298
 1299
 1300
 1301
 1302
 1303
 1304
 1305
 1306
 1307
 1308
 1309
 1310
 1311
 1312
 1313
 1314
 1315
 1316
 1317
 1318
 1319
 1320
 1321
 1322
 1323
 1324
 1325
 1326
 1327
 1328
 1329
 1330
 1331
 1332
 1333
 1334
 1335
 1336
 1337
 1338
 1339
 1340
 1341
 1342
 1343
 1344
 1345
 1346
 1347
 1348
 1349
 1350
 1351
 1352
 1353
 1354
 1355
 1356
 1357
 1358
 1359
 1360
 1361
 1362
 1363
 1364
 1365
 1366
 1367
 1368
 1369
 1370
 1371
 1372
 1373
 1374
 1375
 1376
 1377

Fig. 8 shows a schematic arrangement of an exemplary magnetic recording apparatus according to a second embodiment of the present invention as viewed from a position thereover.

Fig. 9 shows a sectional view as viewed in a direction of A-A' illustrating the magnetic recording apparatus shown in Fig. 8.

Fig. 10 shows a schematic sectional view illustrating a magnetic disk produced in a third embodiment of the present invention.

Fig. 11 shows graphs illustrating a hysteresis loop (major loop) of the magnetic disk shown in Fig. 10, and a magnified view of a minor loop of the hysteresis loop.

Fig. 12 shows a schematic sectional view illustrating a modified embodiment of the magnetic disk according to the third embodiment of the present invention.

Fig. 13 shows a schematic sectional view illustrating another modified embodiment of the magnetic disk according to the third embodiment of the present invention.

Fig. 14 shows a graph illustrating a hysteresis loop (major loop) of a magnetic disk according to a fourth embodiment.

Fig. 15 shows a graph illustrating a relationship between a film thickness of a lattice spacing-adjusting layer and a coercive force of a recording layer and a relationship between the film thickness of the lattice spacing-adjusting layer and an exchange coupling magnetic field concerning the magnetic disk according to the fourth embodiment.

Fig. 16 schematically shows a minor loop of the hysteresis loop shown in Fig. 2.

Fig. 17A shows a graph illustrating the change of exchange coupling energy with respect to the ferromagnetic atom (Co) concentration of a ferromagnetic atom-rich layer, and Fig. 17B shows a graph illustrating the change of $(K_u \cdot V)/k_B \cdot T$ with respect to the ferromagnetic atom (Co) concentration of the ferromagnetic atom-rich layer.